



## CRANE DATA

### 1 General

Crane type .....KD10t x10.5m Hol:12m  
Span .....10.5m  
Crane load (SWL) .....10000kg  
Number of hoists .....1 ps  
Hoisting height .....12m (max12m)  
Hoist type .....H4104D0100M512CD05N  
Trolley rail gauge .....1700mm  
Crane use .....Indoor

Crane group .....FEM A5  
Hoist group .....M5(FEM 2m)  
Hoist traversing group .....M5(FEM 2m)  
Bridge traveling group .....M5(FEM 2m)

Hoisting speed .....4/0.7 2-speed  
Trolley traversing speed .....0-20 m/min Stepless  
Bridge traveling speed .....0-32 m/min Stepless

Dynamic coefficient for load .....1.18  
Dynamic coefficient dead load .....1.1  
Sideways pull factor .....N/A  
Crane acceleration .....0.12m/s<sup>2</sup>

Weight of crane (with hoists) .....4852 kg  
Weight of crane bridge (without hoists) .....3921 kg  
Weight of one hoist and trolley .....931 kg  
Weight of one end carriage .....315 kg  
Weight of one crane traveling machinery .....20 kg  
Weight of bridge panel .....50kg  
Weight of one main girder .....1088 kg  
Weight of crane service platform .....745 kg

Main girder type (Box) .....300/490/6/8/6/8-Q235  
Service platform type .....Bottom joint  
Surface preparation type .....Sa2.5  
Painting type .....Epoxy

### 2 Electrical

Main voltage .....380V/50Hz  
Control voltage .....48AC  
Nominal power of crane .....11.6kW  
Maximum current of crane\*) .....N/A  
Nominal current of crane\*) .....28.4Ass  
Power factor at starting current .....0.77  
Power factor at nominal current .....0.93  
Voltage drop of trolley power supply .....<= 2%  
Voltage drop of crane power supply .....N/A

Calculation number: Cal\_KD10t-10.5-12m  
Crane work number: KD10t x10.5m Hol:12m  
User/Version: RUSAT/ 4.0.39D  
Printing date: 2024/02/09  
Printing time: 13:37