



CRANE DATA

Calculation number: Cal_KU8t-4.2-9.5m
Crane work number: 8t x4.2m Hol:9.5m
User/Version: 14:12
Printing date: 2024/03/22
Printing time: 14:12

KU8t x 4.2m Hol:9.5m

1 General

Crane load (SWL)	8 000 kg
Span	4.2 m
Hoisting height	9.5 m (Max12 m)
Crane group	FEM A5
Hoist group	FEM M6 (3m)
Bridge traversing group	FEM M5 (2m)
Trolley traversing group	FEM M5 (2m)
Hoisting speed	4/0.7 m/min
Trolley traversing speed	0-20 m/min
Bridge traveling speed	0-20 m/min
Weight of crane (with hoists)	2320 kg
Weight of one hoist and trolley	750 kg
Weight of one main girder.....	730 kg
Weight of Service platform	N/A
Main girder type (Box)	410/490/6/30/6/6-Q235
Surface preparation type	Shot Blasting Sa2.5
Painting type/depth	E/120 µm
Runway rail type.....	
Max./Min. static wheel load	28.50/4.68 kN
Buffer diameter/center Height.....	63 mm/119 mm

2 Crane control

Control method.....	Pendant
---------------------	---------

3 Electrical

Main/Control voltage	380 V/50 Hz/48 AC V
Nominal power of crane	9.9 kW
Max./Nominal current of crane*).....	101.2 A/23.2 A

4 Hoisting motor

Motor type/code/Number	SD05/AD195X222N/1set
Duty group	FEM M6 (3m)
Nominal power.....	7.5/1.2 kW
Duty factor	60 % ED

5 Trolley traversing motor

Motor type/Number.....	AF115X411N/1set
Duty group	FEM M5 (2m)
Nominal power.....	1.1 kW
Duty factor	40 % ED

6 Bridge traveling motor

Motor type/Number.....	AF115L411N/2set
Duty group	FEM M5 (2m)
Nominal power.....	0.65 kW
Duty factor	40 % ED