

## CRANE DATA

### 1 General

Crane type .....	KS3.2t x16.5m Hol:9.5m	
Span .....	16.5m	
Crane load (SWL) .....	3200kg	
Number of hoists .....	1 ps	
Hoisting height .....	9.5m (max9.5m)	
Hoist type.....	K2104L0032M509DD02N	
Trolley rail gauge.....	N/A	
Crane use .....	Indoor	
Crane group.....	FEM A5	
Hoist group .....	M5(FEM 2m)	
Hoist traversing group .....	M5(FEM 2m)	
Bridge traveling group .....	M5(FEM 2m)	
Hoisting speed .....	5/0.8	2-speed
Trolley traversing speed .....	0-20 m/min	Stepless
Bridge traveling speed .....	0-32 m/min	Stepless
Dynamic coefficient for load .....	1.19	
Dynamic coefficient dead load .....	1.1	
Sideways pull factor .....	N/A	
Crane acceleration .....	0.13m/s <sup>2</sup>	
Weight of crane (with hoists).....	2800 kg	
Weight of crane bridge (without hoists) .....	2527 kg	
Weight of one hoist and trolley .....	273 kg	
Weight of one end carriage.....	125 kg	
Weight of one crane traveling machinery .....	14 kg	
Weight of bridge panel .....	50kg	
Weight of one main girder .....	1939 kg	
Weight of crane service platform .....	N/A	
Main girder type (Box) .....	300/610/6/16/6/6-Q235	
Service platform type .....	N/A	
Surface preparation type .....	Sa2.5	
Painting type .....	Epoxy	

### 2 Electrical

Main voltage .....	380V/50Hz
Control voltage .....	48AC
Nominal power of crane .....	4.95kW
Maximum current of crane*) .....	N/A
Nominal current of crane*) .....	12.8Ass
Power factor at starting current .....	0.83
Power factor at nominal current.....	0.92
Voltage drop of trolley power supply .....	<= 2%
Voltage drop of crane power supply .....	N/A