

CRANE DATA

1 General

Crane type	KS12.5t x12m Hol:12m	
Span	12m	
Crane load (SWL)	12500kg	
Number of hoists	1 ps	
Hoisting height	12m (max12m)	
Hoist type	H4104L0125M412CD05N	
Trolley rail gauge	N/A	
Crane use	Indoor	
Crane group	FEM A5	
Hoist group	M4(FEM 1Am)	
Hoist traversing group	M5(FEM 2m)	
Bridge traveling group	M5(FEM 2m)	
Hoisting speed	4/0.7	2-speed
Trolley traversing speed	0-20 m/min	Stepless
Bridge traveling speed	0-32 m/min	Stepless
Dynamic coefficient for load	1.18	
Dynamic coefficient dead load	1.1	
Sideways pull factor	N/A	
Crane acceleration	0.12m/s ²	
Weight of crane (with hoists)	4520 kg	
Weight of crane bridge (without hoists)	3780 kg	
Weight of one hoist and trolley	740 kg	
Weight of one end carriage	285 kg	
Weight of one crane traveling machinery	20 kg	
Weight of bridge panel	50kg	
Weight of one main girder	2884 kg	
Weight of crane service platform	N/A	
Main girder type (Box)	410/860/6/32/6/8-Q235	
Service platform type	N/A	
Surface preparation type	Sa2.5	
Painting type	Epoxy	

2 Electrical

Main voltage	380V/50Hz	
Control voltage	48AC	
Nominal power of crane	11.4kW	
Maximum current of crane*)	N/A	
Nominal current of crane*)	27.2Ass	
Power factor at starting current	0.77	
Power factor at nominal current	0.93	
Voltage drop of trolley power supply	<= 2%	
Voltage drop of crane power supply	N/A	