

## **CRANE DATA**

### **1 General**

Crane type .....	KS6.3t x8m Hol:12m	
Span .....	8m	
Crane load (SWL) .....	6300kg	
Number of hoists .....	1 ps	
Hoisting height .....	12m (max12m)	
Hoist type.....	H4104L0063M612CD05N	
Trolley rail gauge.....	N/A	
Crane use .....	Indoor	
Crane group.....	FEM A5	
Hoist group .....	M6(FEM 3m)	
Hoist traversing group .....	M5(FEM 2m)	
Bridge traveling group .....	M5(FEM 2m)	
Hoisting speed .....	4/0.7	2-speed
Trolley traversing speed .....	0-20 m/min	Stepless
Bridge traveling speed .....	0-32 m/min	Stepless
Dynamic coefficient for load .....	1.18	
Dynamic coefficient dead load .....	1.1	
Sideways pull factor .....	N/A	
Crane acceleration .....	0.08m/s <sup>2</sup>	
Weight of crane (with hoists).....	2755 kg	
Weight of crane bridge (without hoists) .....	2015 kg	
Weight of one hoist and trolley .....	740 kg	
Weight of one end carriage.....	208 kg	
Weight of one crane traveling machinery .....	14 kg	
Weight of bridge panel .....	50kg	
Weight of one main girder .....	1313 kg	
Weight of crane service platform .....	N/A	
Main girder type (Box) .....	410/490/6/25/6/6-Q235	
Service platform type .....	N/A	
Surface preparation type .....	Sa2.5	
Painting type .....	Epoxy	

### **2 Electrical**

Main voltage .....	380V/50Hz	
Control voltage .....	48AC	
Nominal power of crane .....	9.2kW	
Maximum current of crane*) .....	N/A	
Nominal current of crane*) .....	21.4Ass	
Power factor at starting current .....	0.77	
Power factor at nominal current.....	0.87	
Voltage drop of trolley power supply .....	<= 2%	
Voltage drop of crane power supply .....	N/A	