



CRANE DATA

Calculation number: Cal_KS5t-25-12m
Crane work number: KS5t x25m Hol:12m
User/Version: RUSAT/ 4.0.39D
Printing date: 2024/03/20
Printing time: 19:44

1 General

Crane typeKS5t x25m Hol:12m
Span25m
Crane load (SWL)5000kg
Number of hoists1 ps
Hoisting height12m (max12m)
Hoist typeK3104L0050M512DD03N
Trolley rail gaugeN/A
Crane useIndoor

Crane groupFEM A5
Hoist groupM5(FEM 2m)
Hoist traversing groupM5(FEM 2m)
Bridge traveling groupM5(FEM 2m)

Hoisting speed5/0.8 2-speed
Trolley traversing speed0-20 m/min Stepless
Bridge traveling speed0-32 m/min Stepless

Dynamic coefficient for load1.19
Dynamic coefficient dead load1.1
Sideways pull factorN/A
Crane acceleration0.12m/s²

Weight of crane (with hoists)6890 kg
Weight of crane bridge (without hoists)6503 kg
Weight of one hoist and trolley387 kg
Weight of one end carriage351 kg
Weight of one crane traveling machinery20 kg
Weight of bridge panel50kg
Weight of one main girder5348 kg
Weight of crane service platformN/A

Main girder type (Box)410/860/6/22/6/10-Q235
Service platform typeN/A
Surface preparation typeSa2.5
Painting typeEpoxy

2 Electrical

Main voltage380V/50Hz
Control voltage48AC
Nominal power of crane6.95kW
Maximum current of crane*)N/A
Nominal current of crane*)16.3Ass
Power factor at starting current0.84
Power factor at nominal current0.93
Voltage drop of trolley power supply<= 2%
Voltage drop of crane power supplyN/A