

## CRANE DATA

### 1 General

Crane type .....	KS3.2t x12m Hol:6m
Span .....	12m
Crane load (SWL) .....	3200kg
Number of hoists .....	1 ps
Hoisting height .....	6m (max6m)
Hoist type.....	K2104L0032M506DD02N
Trolley rail gauge.....	N/A
Crane use .....	Indoor
Crane group.....	FEM A5
Hoist group .....	M5(FEM 2m)
Hoist traversing group .....	M5(FEM 2m)
Bridge traveling group .....	M5(FEM 2m)
Hoisting speed .....	5/0.8      2-speed
Trolley traversing speed .....	0-20 m/min      Stepless
Bridge traveling speed .....	0-32 m/min      Stepless
Dynamic coefficient for load .....	1.19
Dynamic coefficient dead load .....	1.1
Sideways pull factor .....	N/A
Crane acceleration .....	0.13m/s <sup>2</sup>
Weight of crane (with hoists).....	2095 kg
Weight of crane bridge (without hoists) .....	1846 kg
Weight of one hoist and trolley .....	249 kg
Weight of one end carriage.....	108 kg
Weight of one crane traveling machinery .....	14 kg
Weight of bridge panel .....	50kg
Weight of one main girder .....	1323 kg
Weight of crane service platform .....	N/A
Main girder type (Box) .....	300/490/6/18/6/6-Q235
Service platform type .....	N/A
Surface preparation type.....	Sa2.5
Painting type .....	Epoxy

### 2 Electrical

Main voltage .....	380V/50Hz
Control voltage .....	48AC
Nominal power of crane .....	4.95kW
Maximum current of crane*) .....	N/A
Nominal current of crane*) .....	12.8Ass
Power factor at starting current.....	0.83
Power factor at nominal current.....	0.92
Voltage drop of trolley power supply .....	<= 2%
Voltage drop of crane power supply .....	N/A