

CRANE DATA

1 General

Crane typeKS5t x19.5m Hol:12m
 Span19.5m
 Crane load (SWL)5000kg
 Number of hoists1 ps
 Hoisting height12m (max12m)
 Hoist typeK3104L0050M512DD03N
 Trolley rail gaugeN/A
 Crane useIndoor

 Crane groupFEM A5
 Hoist groupM5(FEM 2m)
 Hoist traversing groupM5(FEM 2m)
 Bridge traveling groupM5(FEM 2m)

 Hoisting speed5/0.8 2-speed
 Trolley traversing speed0-20 m/min Stepless
 Bridge traveling speed0-32 m/min Stepless

 Dynamic coefficient for load1.19
 Dynamic coefficient dead load1.1
 Sideways pull factorN/A
 Crane acceleration0.12m/s²

 Weight of crane (with hoists)4792 kg
 Weight of crane bridge (without hoists)4405 kg
 Weight of one hoist and trolley387 kg
 Weight of one end carriage208 kg
 Weight of one crane traveling machinery14 kg
 Weight of bridge panel50kg
 Weight of one main girder3627 kg
 Weight of crane service platformN/A

 Main girder type (Box)410/740/6/22/6/8-Q235
 Service platform typeN/A
 Surface preparation typeSa2.5
 Painting typeEpoxy

2 Electrical

Main voltage380V/50Hz
 Control voltage48AC
 Nominal power of crane6.95kW
 Maximum current of crane*)N/A
 Nominal current of crane*)16.3Ass
 Power factor at starting current0.84
 Power factor at nominal current0.93
 Voltage drop of trolley power supply<= 2%
 Voltage drop of crane power supplyN/A