

CRANE DATA

1 General

Crane type	KD6.3t x22.5m Hol:12m	
Span	22.5m	
Crane load (SWL)	6300kg	
Number of hoists	1 ps	
Hoisting height	12m (max12m)	
Hoist type.....	H4104D0063M612FD06N	
Trolley rail gauge.....	1700mm	
Crane use	Indoor	
Crane group.....	FEM A5	
Hoist group	M6(FEM 3m)	
Hoist traversing group	M5(FEM 2m)	
Bridge traveling group	M5(FEM 2m)	
Hoisting speed	8/1.3	2-speed
Trolley traversing speed	0-20 m/min	Stepless
Bridge traveling speed	0-32 m/min	Stepless
Dynamic coefficient for load	1.22	
Dynamic coefficient dead load	1.1	
Sideways pull factor	N/A	
Crane acceleration	0.12m/s ²	
Weight of crane (with hoists)	12186 kg	
Weight of crane bridge (without hoists)	11255 kg	
Weight of one hoist and trolley	931 kg	
Weight of one end carriage.....	608 kg	
Weight of one crane traveling machinery	20 kg	
Weight of bridge panel	50kg	
Weight of one main girder	3877 kg	
Weight of crane service platform	1597 kg	
Main girder type (Box)	410/860/6/8/6/8-Q235	
Service platform type	Bottom joint	
Surface preparation type	Sa2.5	
Painting type	Epoxy	

2 Electrical

Main voltage	380V/50Hz	
Control voltage	48AC	
Nominal power of crane	15.5kW	
Maximum current of crane*)	N/A	
Nominal current of crane*)	36.2Ass	
Power factor at starting current	0.67	
Power factor at nominal current	0.82	
Voltage drop of trolley power supply	<= 2%	
Voltage drop of crane power supply	N/A	