



## CRANE DATA

### 1 General

Crane type .....KS5t x7.5m Hol:12m  
Span .....7.5m  
Crane load (SWL) .....5000kg  
Number of hoists .....1 ps  
Hoisting height .....12m (max12m)  
Hoist type .....K3104L0050M512DD03N  
Trolley rail gauge .....N/A  
Crane use .....Indoor

Crane group .....FEM A5  
Hoist group .....M5(FEM 2m)  
Hoist traversing group .....M5(FEM 2m)  
Bridge traveling group .....M5(FEM 2m)

Hoisting speed .....5/0.8 2-speed  
Trolley traversing speed .....0-20 m/min Stepless  
Bridge traveling speed .....0-32 m/min Stepless

Dynamic coefficient for load .....1.19  
Dynamic coefficient dead load .....1.1  
Sideways pull factor .....N/A  
Crane acceleration .....0.13m/s<sup>2</sup>

Weight of crane (with hoists) .....1729 kg  
Weight of crane bridge (without hoists) .....1342 kg  
Weight of one hoist and trolley .....387 kg  
Weight of one end carriage .....108 kg  
Weight of one crane traveling machinery .....14 kg  
Weight of bridge panel .....50kg  
Weight of one main girder .....843 kg  
Weight of crane service platform .....N/A

Main girder type (Box) .....300/410/6/22/6/6-Q235  
Service platform type .....N/A  
Surface preparation type .....Sa2.5  
Painting type .....Epoxy

### 2 Electrical

Main voltage .....380V/50Hz  
Control voltage .....48AC  
Nominal power of crane .....6.25kW  
Maximum current of crane\*) .....N/A  
Nominal current of crane\*) .....14.5Ass  
Power factor at starting current .....0.84  
Power factor at nominal current .....0.93  
Voltage drop of trolley power supply .....<= 2%  
Voltage drop of crane power supply .....N/A

Calculation number: Cal\_KS5t-7.5-12m  
Crane work number: KS5t x7.5m Hol:12m  
User/Version: RUSAT/ 4.0.39D  
Printing date: 2024/02/08  
Printing time: 14:13