



CRANE DATA

Calculation number: Cal_KU8t-12-12m
Crane work number: 8t x12m Hol:12m
User/Version: 14:49
Printing date: 2024/03/22
Printing time: 14:49

KU8t x 12m Hol:12m

1 General

Crane load (SWL) 8 000 kg
Span 12 m
Hoisting height 12 m (Max12 m)

Crane group FEM A5
Hoist group FEM M6 (3m)
Bridge traversing group FEM M5 (2m)
Trolley traversing group FEM M5 (2m)

Hoisting speed 4/0.7 m/min 2-speed
Trolley traversing speed 0-20 m/min Stepless
Bridge traveling speed 0-20 m/min Stepless

Weight of crane (with hoists) 3930 kg
Weight of one hoist and trolley 750 kg
Weight of one main girder 2290 kg
Weight of Service platform N/A

Main girder type (Box) 410/610/6/30/6/6-Q235
Surface preparation type Shot Blasting Sa2.5
Painting type/depth E/120 µm
Runway rail type
Max./Min. static wheel load 48.18/9.32 kN
Buffer diameter/center Height 63 mm/119 mm

2 Crane control

Control method Pendant

3 Electrical

Main/Control voltage 380 V/50 Hz/48 AC V
Nominal power of crane 9.9 kW
Max./Nominal current of crane*) 101.2 A/23.2 A

4 Hoisting motor

Motor type/code/Number SD05/AD195X222N/1set
Duty group FEM M6 (3m)
Nominal power 7.5/1.2 kW
Duty factor **60 % ED**

5 Trolley traversing motor

Motor type/Number AF115X411N/1set
Duty group FEM M5 (2m)
Nominal power 1.1 kW
Duty factor **40 % ED**

6 Bridge traveling motor

Motor type/Number AF115L411N/2set
Duty group FEM M5 (2m)
Nominal power 0.65 kW
Duty factor **40 % ED**