

## CRANE DATA

### 1 General

Crane type .....	KD10t x25m Hol:12m	
Span .....	25m	
Crane load (SWL) .....	10000kg	
Number of hoists .....	1 ps	
Hoisting height .....	12m (max12m)	
Hoist type .....	H4104D0100M512CD05N	
Trolley rail gauge .....	1700mm	
Crane use .....	Indoor	
Crane group .....	FEM A5	
Hoist group .....	M5(FEM 2m)	
Hoist traversing group .....	M5(FEM 2m)	
Bridge traveling group .....	M5(FEM 2m)	
Hoisting speed .....	4/0.7	2-speed
Trolley traversing speed .....	0-20 m/min	Stepless
Bridge traveling speed .....	0-32 m/min	Stepless
Dynamic coefficient for load .....	1.18	
Dynamic coefficient dead load .....	1.1	
Sideways pull factor .....	N/A	
Crane acceleration .....	0.12m/s <sup>2</sup>	
Weight of crane (with hoists) .....	14014 kg	
Weight of crane bridge (without hoists) .....	13083 kg	
Weight of one hoist and trolley .....	931 kg	
Weight of one end carriage .....	351 kg	
Weight of one crane traveling machinery .....	20 kg	
Weight of bridge panel .....	50kg	
Weight of one main girder .....	4927 kg	
Weight of crane service platform .....	1775 kg	
Main girder type (Box) .....	410/1080/6/8/6/8-Q235	
Service platform type .....	Bottom joint	
Surface preparation type .....	Sa2.5	
Painting type .....	Epoxy	

### 2 Electrical

Main voltage .....	380V/50Hz	
Control voltage .....	48AC	
Nominal power of crane .....	12.5kW	
Maximum current of crane*) .....	N/A	
Nominal current of crane*) .....	30.2Ass	
Power factor at starting current .....	0.77	
Power factor at nominal current .....	0.93	
Voltage drop of trolley power supply .....	<= 2%	
Voltage drop of crane power supply .....	N/A	