



CRANE DATA

1 General

Crane typeKD25t x16.5m Hol:12m
Span16.5m
Crane load (SWL)25000kg
Number of hoists1 ps
Hoisting height12m (max12m)
Hoist typeK5106D0250M512AD06N
Trolley rail gauge2400mm
Crane useIndoor

Crane groupFEM A5
Hoist groupM5(FEM 2m)
Hoist traversing groupM5(FEM 2m)
Bridge traveling groupM5(FEM 2m)

Hoisting speed2.5/0.4 2-speed
Trolley traversing speed0-20 m/min Stepless
Bridge traveling speed0-32 m/min Stepless

Dynamic coefficient for load1.17
Dynamic coefficient dead load1.1
Sideways pull factorN/A
Crane acceleration0.12m/s²

Weight of crane (with hoists)10848 kg
Weight of crane bridge (without hoists)8909 kg
Weight of one hoist and trolley1939 kg
Weight of one end carriage389 kg
Weight of one crane traveling machinery20 kg
Weight of bridge panel50kg
Weight of one main girder3196 kg
Weight of crane service platform1171 kg

Main girder type (Box)410/980/6/8/6/8-Q235
Service platform typeBottom joint
Surface preparation typeSa2.5
Painting typeEpoxy

2 Electrical

Main voltage380V/50Hz
Control voltage48AC
Nominal power of crane18.9kW
Maximum current of crane*)N/A
Nominal current of crane*)44.6Ass
Power factor at starting current0.67
Power factor at nominal current0.91
Voltage drop of trolley power supply<= 2%
Voltage drop of crane power supplyN/A

Calculation number: Cal_KD25t-16.5-12m
Crane work number: KD25t x16.5m Hol:12m
User/Version: RUSAT/ 4.0.39D
Printing date: 2024/02/12
Printing time: 21:10