



Type/型号	SEC154BK
Power/Supply/供电	380V/50HZ
Motor Power/额定功率	3.3kw/50HZ
Speed/转速/50HZ时	1320 RPM
额定转矩/额定	0.1
输出轴转速/50HZ时	1342 RPM
CDF/负载持续率	符合国家标准
Insulation/绝缘等级	F
Working Current/工作电流	6.1A
效率	89%
额定功率因数	0.72
重量	6.8kg

Type/型号	6F132M6-50HZ
Power/Supply/供电	380V/50HZ
Motor Power/额定功率	4.2kw
Speed/转速/50HZ时	1384 RPM/50HZ
额定转矩/额定	0.1
输出轴转速/50HZ时	1377 RPM
CDF/负载持续率	符合国家标准
Insulation/绝缘等级	F
Working Current/工作电流	10.2 A
效率	79%
额定功率因数	0.76

EC34-130-DF50LD1-2500+2500H3-L1000

Type/型号	名称/Name	数量	尺寸/Dimension	材料/Material	重量/Weight	备注/Remark
DF50LD1-2500+2500	未注公差尺寸的机加工零件	板金件及?件	?号:	漆: 1/1	参照??	比例
SWL/安全起重量	0.5...3	±0.1	±0.15			
FEM/利用等级	-3...6	±0.1	±0.2			
Power/电机功率	>6...30	±0.2	±0.5			
Lifting Speed/起升速度	>30...120	±0.3	±0.8			
Chain/链条规格	11.3x31x11.3x31	±0.5	±1.2			
Chain falls/环链倍率	1/1 +1/1	>315...1000	±0.8	±2		
Weight/重量(3m吊高)	339.1 kg	>1000...2000	±1.2	±3		

上海德益起重机械有限公司
Shanghai DELIC Light Crane Co., Ltd.
EC34-DF50LD1-2500+2500 DF50LD1-2500+2500