



CRANE DATA

1 General

Crane typeKD30t x16.5m Hol:12m
Span16.5m
Crane load (SWL)30000kg
Number of hoists1 ps
Hoisting height12m (max12m)
Hoist typeK5106D0300M412AD06N
Trolley rail gauge2400mm
Crane useIndoor

Crane groupFEM A5
Hoist groupM4(FEM 1Am)
Hoist traversing groupM5(FEM 2m)
Bridge traveling groupM5(FEM 2m)

Hoisting speed2.5/0.4 2-speed
Trolley traversing speed0-20 m/min Stepless
Bridge traveling speed0-32 m/min Stepless

Dynamic coefficient for load1.17
Dynamic coefficient dead load1.1
Sideways pull factorN/A
Crane acceleration0.12m/s²

Weight of crane (with hoists)11402 kg
Weight of crane bridge (without hoists)9463 kg
Weight of one hoist and trolley1939 kg
Weight of one end carriage388 kg
Weight of one crane traveling machinery20 kg
Weight of bridge panel50kg
Weight of one main girder3473 kg
Weight of crane service platform1171 kg

Main girder type (Box)410/1080/6/8/6/10-Q235
Service platform typeBottom joint
Surface preparation typeSa2.5
Painting typeEpoxy

2 Electrical

Main voltage380V/50Hz
Control voltage48AC
Nominal power of crane20.7kW
Maximum current of crane*)N/A
Nominal current of crane*)48.2Ass
Power factor at starting current0.67
Power factor at nominal current0.91
Voltage drop of trolley power supply<= 2%
Voltage drop of crane power supplyN/A

Calculation number: Cal_KD30t-16.5-12m
Crane work number: KD30t x16.5m Hol:12m
User/Version: RUSAT/ 4.0.39D
Printing date: 2024/02/15
Printing time: 13:44