



## CRANE DATA

### 1 General

Crane type .....KD32t x25m Hol:12m  
Span .....25m  
Crane load (SWL) .....32000kg  
Number of hoists .....1 ps  
Hoisting height .....12m (max12m)  
Hoist type .....K5108D0320M512AD06N  
Trolley rail gauge .....3100mm  
Crane use .....Indoor

Crane group .....FEM A5  
Hoist group .....M5(FEM 2m)  
Hoist traversing group .....M5(FEM 2m)  
Bridge traveling group .....M5(FEM 2m)

Hoisting speed .....2/0.3 2-speed  
Trolley traversing speed .....0-20 m/min Stepless  
Bridge traveling speed .....0-32 m/min Stepless

Dynamic coefficient for load .....1.17  
Dynamic coefficient dead load .....1.1  
Sideways pull factor .....N/A  
Crane acceleration .....0.12m/s<sup>2</sup>

Weight of crane (with hoists) .....19905 kg  
Weight of crane bridge (without hoists) .....17656 kg  
Weight of one hoist and trolley .....2249 kg  
Weight of one end carriage .....670 kg  
Weight of one crane traveling machinery .....20 kg  
Weight of bridge panel .....50kg  
Weight of one main girder .....6873 kg  
Weight of crane service platform .....1775 kg

Main girder type (Box) .....490/1480/6/8/6/10-Q235  
Service platform type .....Side joint  
Surface preparation type .....Sa2.5  
Painting type .....Epoxy

### 2 Electrical

Main voltage .....380V/50Hz  
Control voltage .....48AC  
Nominal power of crane .....21.6kW  
Maximum current of crane\*) .....N/A  
Nominal current of crane\*) .....50Ass  
Power factor at starting current .....0.67  
Power factor at nominal current .....0.91  
Voltage drop of trolley power supply .....<= 2%  
Voltage drop of crane power supply .....N/A

Calculation number: Cal\_KD32t-25-12m  
Crane work number: KD32t x25m Hol:12m  
User/Version: 18:35  
Printing date: 2024/02/15  
Printing time: 18:35