

CRANE DATA

1 General

Crane load (SWL)	8 000 kg	
Span	6 m	
Hoisting height	9.5 m (Max12 m)	
Crane group	FEM A5	
Hoist group	FEM M6 (3m)	
Bridge traversing group	FEM M5 (2m)	
Trolley traversing group	FEM M5 (2m)	
Hoisting speed	4/0.7 m/min	2-speed
Trolley traversing speed	0-20 m/min	Stepless
Bridge traveling speed	0-20 m/min	Stepless
Weight of crane (with hoists)	2680 kg	
Weight of one hoist and trolley	750 kg	
Weight of one main girder	1070 kg	
Weight of Service platform	N/A	
Main girder type (Box)	410/490/6/30/6/6-Q235	
Surface preparation type	Shot Blasting Sa2.5	
Painting type/depth	E/120 µm	
Runway rail type		
Max./Min. static wheel load	40.71/6.69 kN	
Buffer diameter/center Height	63 mm/119 mm	

2 Crane control

Control method	Pendant
----------------------	---------

3 Electrical

Main/Control voltage	380 V/50 Hz/48 AC V
Nominal power of crane	9.9 kW
Max./Nominal current of crane*)	101.2 A/23.2 A

4 Hoisting motor

Motor type/code/Number	SD05/AD195X222N/1set
Duty group	FEM M6 (3m)
Nominal power	7.5/1.2 kW
Duty factor	60 % ED

5 Trolley traversing motor

Motor type/Number	AF115X411N/1set
Duty group	FEM M5 (2m)
Nominal power	1.1 kW
Duty factor	40 % ED

6 Bridge traveling motor

Motor type/Number	AF115L411N/2set
Duty group	FEM M5 (2m)
Nominal power	0.65 kW
Duty factor	40 % ED