

## CRANE DATA

### 1 General

Crane type .....	KD32t x19.5m Hol:12m	
Span .....	19.5m	
Crane load (SWL) .....	32000kg	
Number of hoists .....	1 ps	
Hoisting height .....	12m (max12m)	
Hoist type .....	K5108D0320M512AD06N	
Trolley rail gauge .....	3100mm	
Crane use .....	Indoor	
Crane group .....	FEM A5	
Hoist group .....	M5(FEM 2m)	
Hoist traversing group .....	M5(FEM 2m)	
Bridge traveling group .....	M5(FEM 2m)	
Hoisting speed .....	2/0.3	2-speed
Trolley traversing speed .....	0-20 m/min	Stepless
Bridge traveling speed .....	0-32 m/min	Stepless
Dynamic coefficient for load .....	1.17	
Dynamic coefficient dead load .....	1.1	
Sideways pull factor .....	N/A	
Crane acceleration .....	0.12m/s <sup>2</sup>	
Weight of crane (with hoists) .....	16739 kg	
Weight of crane bridge (without hoists) .....	14490 kg	
Weight of one hoist and trolley .....	2249 kg	
Weight of one end carriage .....	1516 kg	
Weight of one crane traveling machinery .....	38 kg	
Weight of bridge panel .....	50kg	
Weight of one main girder .....	4677 kg	
Weight of crane service platform .....	1384 kg	
Main girder type (Box) .....	490/1230/6/8/6/10-Q235	
Service platform type .....	Bottom joint	
Surface preparation type .....	Sa2.5	
Painting type .....	Epoxy	

### 2 Electrical

Main voltage .....	380V/50Hz	
Control voltage .....	48AC	
Nominal power of crane .....	21.6kW	
Maximum current of crane*) .....	N/A	
Nominal current of crane*) .....	50Ass	
Power factor at starting current .....	0.67	
Power factor at nominal current .....	0.91	
Voltage drop of trolley power supply .....	<= 2%	
Voltage drop of crane power supply .....	N/A	