

CRANE DATA

1 General

Crane typeKS20t x22.5m Hol:12m
 Span22.5m
 Crane load (SWL)20000kg
 Number of hoists1 ps
 Hoisting height12m (max12m)
 Hoist typeK5104N0200M412CD06N
 Trolley rail gaugeN/A
 Crane useIndoor

Crane groupFEM A5
 Hoist groupM4(FEM 1Am)
 Hoist traversing groupM5(FEM 2m)
 Bridge traveling groupM5(FEM 2m)

Hoisting speed	4/0.7	2-speed
Trolley traversing speed	0-20 m/min	Stepless
Bridge traveling speed	0-32 m/min	Stepless

Dynamic coefficient for load1.18
 Dynamic coefficient dead load1.1
 Sideways pull factorN/A
 Crane acceleration0.08m/s²

Weight of crane (with hoists)11526 kg
 Weight of crane bridge (without hoists)9916 kg
 Weight of one hoist and trolley1610 kg
 Weight of one end carriage622 kg
 Weight of one crane traveling machinery20 kg
 Weight of bridge panel50kg
 Weight of one main girder8252 kg
 Weight of crane service platformN/A

Main girder type (Box)610/1230/6/32/6/12-Q235
 Service platform typeN/A
 Surface preparation typeSa2.5
 Painting typeEpoxy

2 Electrical

Main voltage380V/50Hz
 Control voltage48AC
 Nominal power of crane19.8kW
 Maximum current of crane*)N/A
 Nominal current of crane*)46.9Ass
 Power factor at starting current0.67
 Power factor at nominal current0.91
 Voltage drop of trolley power supply<= 2%
 Voltage drop of crane power supplyN/A